



## FICHA TECNICA\_CURTIDOS

### 12.7.4 PELLFIX RE-04

**BARRACHINA'S**

---

ASPECT: Milky White Liquid

---

SOLIDS: 50% +/- 1%

---

VISCOSITY BROOKFIELD RVT a 23°C (sp. 3/20 rpm, mPa·s): 1.500-2.500 cps

---

PH: 8.0 +/- 0.5

---

PRECAUTIONS: See instructions on the packaging and in the Safety Data Sheet.

---

#### **Characteristics**

PELLFIX RE-04 is an aqueous dispersion of a copolymer of acrylic esters and styrene, free of ethoxylated alkylphenols.

PELLFIX RE-04 is used in the textile and leather industry as a binder for nonwovens and surface coatings, giving them hyphroguous properties.

#### **Aplication Field:**

PELLFIX RE-04 is a water-based resin with a fine particle and high anchorage, suitable for impregnating naps, to which it gives medium hardness and water-repellent properties.

The amount of PELLFIX RE-04 to be applied depends on each particular application, whether it is for surface coatings or for impregnations of fabrics and nonwovens.

For a correct use of the product on a textile support, our recommendation is to first apply a drying process for the total elimination of water and then proceed to the crosslinking process for 3 min. at 140-150 °C.

It is suitable as a foil bonding resin.

#### **Instructions for use:**

Apply to spraying gun, or roller.

#### **Security:**

Look up the general security section.

---

*Barrachinas cannot control the conditions under which its products are used, therefore do not accept responsibilities concerning the results and/or consequences from its usage.*

---

Review date:14/02/24