



TECHNICAL INFORMATION

4. GLOSSES

4.1 GLOSSES IN SOLVENT BASE

4.1.11 LUXSOL 7050

CHARACTERISTICS:

Nitrocellulose solution properly formulated in a solvent medium with silicone-based additives to give a soft and warm touch to leather. Its aspect is of a transparent liquid, lightly yellow, and with the characteristic solvent smell. The gloss obtained is **high** and with a quite nice touch.

APPLICATION FIELD:

The LUXSOL 7050 is specially designed as an anchoring bridge or to get blurred effects about laminates or closed surfaces.

INSTRUCTIONS FOR USE:

After thoroughly cleaning leather from glues and other dirt, and after repairing and leveling if necessary, you will apply Luxsol S-1 with a spraying gun with a nozzle opening of 1,5 mm., with a 2-4 atm. pressure and a proper distance to the shoe. The experience tells us the correct distance is from 25 to 35 cm. It is important to have a good application cabin equipped with an extractor fan, water screen and good light. It is convenient to use a protecting mask.

SECURITY:

Look up the general security section.

REMARKS:

It is convenient to apply a base to leather before gloss application to improve its adherence and ageing.

Barrachinas cannot control the conditions under which its products are used, therefore do not accept responsibilities concerning the results and/or consequences from its usage.

Data of Review: 26/02/26