



BARRACHINA'S

TECHNICAL INFORMATION

4. GLOSSES

4.2 GLOSSES IN WATERY BASE

4.2.18 ECO-LUSTRAFIX A-16

CHARACTERISTICS:

Mixture of acrylic polymers, waxes and leveling and touch additives properly formulated to get a **high power gloss**, with a very natural and nice touch. Its aspect is of a milky yellow liquid with a nice smell.

APPLICATION FIELD:

Full-grain good-quality leathers, when you want **to enhance the leather quality**.

INSTRUCTIONS FOR USE:

After thoroughly cleaning leather from glues and other dirt, and after repairing and leveling colours if necessary, you will apply ECO-LUSTRAFIX A-16 with a spraying gun with a nozzle opening of 1-1,5 mm. at 4-6 atm. of pressure, and a proper distance to the shoe. The experience tells us the correct distance is from 25 to 35 cm.. These glosses have a good advantage: they improve their effects with a good brushing, using a cotton or wool brush impregnated with our BRIGHTENING WAX at 500 to 800 r.p.m. It is important to have a good application cabin, equipped with an extractor fan, water screen and good light. It is convenient to use a protecting mask.

SECURITY:

Look up the general security section.

REMARKS:

It is convenient to apply a base to leather before gloss application to improve its adherence and ageing.

Barrachinas cannot control the conditions under which its products are used, therefore do not accept responsibilities concerning the results and/or consequences from its usage.