



TECHNICAL INFORMATION

7. SPECIAL PRODUCTS

7.20 ECO-CEROXPOL 280

CHARACTERISTICS:

Emulsion of soft natural and synthetic waxes in a watery medium, properly formulated to get a leather with a **waxy-greasy** touch. Its aspect is of a white **liquid**. Gloss is not obtained, for the leather, once the product is applied and dried up, has a **matt and dark aspect** and a greasy touch.

APPLICATION FIELD:

Full-grain and Nubuk leather when you want a fashion dark matt aspect. Also for Pull-up leathers. As you can imagine, the quantity of product to apply to get the desired greasy touch will depend on leather absorption.

INTRUCTIONS FOR USE:

After thoroughly cleaning leather from glues and other dirt (with our NUBUK CLEANER RUBBER), you will apply ECO-CEROXPOL 280 with an **spraying gun** with a nozzle opening of 1 to 1,5 mm. and a pressure of 4 to 6 atm., from a proper distance. Experience tells us that 25 to 35 cm. is the correct distance. It is important to have an application cabin equipped with a good extractor fan, water screen and good light for the application to be correct. It is convenient to use protecting mask.

SECURITY:

Look up the general security section.

REMARKS:

Our zone laboratories can offer ECO-CEROXPOL 280 coloured with the desired tone.

Barrachinas cannot control the conditions under which its products are used, therefore do not accept responsibilities concerning the results and/or consequences from its usage.