



BARRACHINA'S

TECHNICAL INFORMATION

7. SPECIAL PRODUCTS

7.8.A. NUBUK PROTECTOR CON FLUOROCARBONOS

H-225

H-245

CHARACTERISTICS:

Mixture of water-repellent and touch agents, with fluorocarbons, conveniently formulated in a solvent medium. Its aspect is of a transparent liquid with an alcohol smell. It brings vigour and richness to leather texture, colour and **superficial resistance to water**, when acting on a Suede-like or Nubuk leather. The main differences between **H-225 y H-245**, is darkness and touch different degrees. That's why it is interesting to test every possibility with our technicians before making a definitive decision.

APPLICATION FIELD:

As its characteristics tell, you will apply it on leathers with a **Suede-like or Nubuk** texture, when enhancing and leveling tone in a shoe is desired. The other effect is protecting the shoe surface from dirt and from water while being used.

INSTRUCTIONS FOR USE:

After thoroughly cleaning leather from glues and other dirt (with our NUBUK CLEANER RUBBER), you will apply Nubuk Protector with a spraying gun with a nozzle opening of 1 to 1,5 mm. and a 4 to 6 atm. pressure, from a proper distance. Experience tells us that 25 to 35 cm. is the correct distance. It is important to have an application cabin equipped with a good extractor fan, water screen and good light for the application to be correct. It is convenient to use a protecting mask.

SECURITY:

Look up the general security section.

REMARKS:

Our zone laboratories can offer any Nubuk Protector from our range.

Barrachinas cannot control the conditions under which its products are used, therefore do not accept responsibilities concerning the results and/or consequences from its usage.

Review date: 12/04/24