



BARRACHINA'S

## TECHNICAL INFORMATION

### 7. SPECIAL PRODUCTS

#### 7.8.B NUBUK PROTECTOR SIN FLUOROCARBONOS

**NP-6/2**  
**H-330/1**  
**H-345**  
**H-350**  
**H-355**

#### **CHARACTERISTICS:**

Mixture of water-repellent and touch agents, fluorocarbon-free, properly formulated in a **solvent medium**. Its aspect is of a transparent liquid with an alcohol smell. It brings vigour and richness to leather texture, colour and **superficial resistance to water**, when acting on a Suede-like or Nubuk leather. The main differences between **NP-6/2, H-330/1, H-345, H-350 y H-355**, is darkness and touch different degrees. That's why it is interesting to test every possibility with our technicians before making a definitive decision.

#### **APPLICATION FIELD:**

As its characteristics tell, you will apply it on leathers with a **Suede-like or Nubuk** texture, when enhancing and leveling tone in a shoe is desired. The other effect is protecting the shoe surface from dirt and from water while being used.

#### **INSTRUCTIONS FOR USE:**

After thoroughly cleaning leather from glues and other dirt (with our NUBUK CLEANER RUBBER), you will apply Nubuk Protector with a spraying gun with a nozzle opening of 1 to 1,5 mm. and a 4 to 6 atm. pressure, from a proper distance. Experience tells us that 25 to 35 cm. is the correct distance. It is important to have an application cabin equipped with a good extractor fan, water screen and good light for the application to be correct. It is convenient to use protecting mask.

#### **SECURITY:**

Look up the general security section.

#### **REMARKS:**

Our zone laboratories can offer any Nubuk Protector from our range.

*Barrachinas cannot control the conditions under which its products are used, therefore do not accept responsibilities concerning the results and/or consequences from its usage.*